



PROTEK-EX DATASHEET

Abstract

This Document refers to a brief technical specification of PROTEK-EX

Holmium Technologies Private Limited
info@holmiumtechnologies.com



Copyright © 2020 Holmium Technologies. All Rights Reserved



Datasheet

Parameters	PROTEK-EX
No of Modbus Slave devices	Up to 8
Digital Input	4 (NO/NC type)
Digital Output	3 (5V DC)
RS-485 port	1 (Master)
SD Card	Yes
Remote Monitoring of PV-DG SYNC*	
Media	GSM (2G/4G) / Wi-Fi / Ethernet
Server	Holmium server Only
Power Supply	
Voltage	12V DC
Current	2A
Communication Protocol	
Modbus Communication	MODBUS RTU/TCP-IP/ SUNSPEC
Server Communication	HTTP/FTP
Protection & Security	
Reverse Polarity Protection	Yes
Surge Protection	Yes
General	
Dimension (W x L x H) mm	600*400*250
IP Grade	IP57
Operating Temperature	0 to 70 ^o C
Humidity	0 to 90%
Display	Yes
Installation	Wall Mounting
Configuration	
Software	KMD Manager
Port	RS-485 Port/ Ethernet

*Remote Monitoring of Solar Plant (Optional)

